



**Vardhan Oil**

# **Vardhan Oil**

*Smooth & Energetic*

Fueling Fabric with **Smooth** Precision  
and **Energetic** Performance



## Overview

**Vardhan Coning Oil** is specially formulated anti-static and anti-splash coning oil. It is recommended for use in Textile Industry as finishing agent. It is highly refined, light coloured, low-viscosity mineral oil-based product containing suitable emulsifier, antistatic, friction reducing and anti-splashing agents to minimize the oil dosage during coning and twisting operation. Vardhan Coning Oil provides excellent lubrication to filaments and reduces friction during operation.

### Technical Specification

Characteristics	Value
Appearance	Clear
Colour	Water White – Pale yellow
Density, g/cc	0.820-0.850
Kinematic Viscosity @40 °C, cst	22 – 25
Emulsion stability, (10% vol. water solution)	Stable
pH Value, (10% vol. Water solution)	6-9

### Vardhan Coning oil Features & Benefits

- Excellent Yarn to Yarn and Yarn to metal lubrication
- Excellent Scour ability
- Excellent Antistatic Properties
- Excellent Stability of the product during storage of lubricated yarns
- Low frictional properties, which ensure smooth running of the yarn in subsequent processing
- Excellent penetrating properties, which ensure uniform oil, pick up throughout the package
- Excellent Non – Corrosive properties
- Formulated for high speed of polyester and nylon filament yarn

**HEALTH & SAFETY:** This product is not likely to present any significant health or safety hazards when properly used in the recommended application and good standards of personal hygiene are maintained. Do not contamination of the other oils, greases, chemicals, and dirty water etc,

**PROTECT THE ENVIRONMENT:** Take used oil to an authorized collection point. Comply with local regulation. Do not discharge into drains, soil or water.

**STORAGE:** We recommend to store all packages under cover. In case outside storage is unavoidable, drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should never be stored above 60°C, exposed to hot sun or freezing conditions.

## Coning Oil

185 KG  
Drum Package



**Mfg.: Shree Vardhan Multitech**

Plot No. C/618-620, Road No. 7, GIDC Sarigam – 396155.

Tal. Umbergaon, Dist. Valsad, Gujarat (India)



[info@vardhanoil.com](mailto:info@vardhanoil.com)



+91 260-2780319



[www.vardhanoil.com](http://www.vardhanoil.com)